


RACCORDI A SALDARE

Welding fittings • Schweissfittings • Raccords à souder • Racores para soldar

**704****CURVA DIMA 3D 90° DA TUBO SENZA SALDATURA**

- SEAMLESS ELBOW 3D 90°
- NAHTLOSE ROHRBÖGEN BA3 90°
- COURBE 3D 90° DE TUBE SANS SOUDURE
- CODO PARA SOLDAR 3D 90° (DE TUBO SIN SOLDATURA)

MATERIAL: P235TR2 - S235 (R.St.37.0)**NORM:** EN 10253-1 (DIN 2605)

CODE	DN	DN inch	DN mm	S mm	R mm	B mm			
704172000*	10	3/8"	17,2	2	19	28	0,04	100	-
704213000	15	1/2"	21,3	2	29	38	0,04	100	9600
704269000	20	3/4"	26,9	2,3	29	43	0,06	100	9600
704337000	25	1"	33,7	2,6	38	56	0,11	80	4480
704424000	32	1"1/4	42,4	2,6	48	70	0,19	100	3600
704483000	40	1"1/2	48,3	2,6	57	83	0,26	50	1800
704570000	-	-	57	2,9	72	100	0,44	25	900
704603000	50	2"	60,3	2,9	76	106	0,49	25	900
704700000	-	-	70	2,9	92	127	0,7	10	720
704761000	65	2"1/2	76,1	2,9	95	132	0,78	5	660
704889000	80	3"	88,9	3,2	114	159	1,22	5	350
704101000	-	3"1/2	101,6	3,6	133	184	1,82	4	192
704108000	-	-	108	3,6	142,5	196	2,07	4	192
704114000	100	4"	114,3	3,6	152	210	2,35	4	192
704133000	-	-	133	4	181	247	3,62	1	90
704139000	125	5"	139,7	4	190	262	4	1	84
704159000	-	-	159	4,5	216	295	5,82	1	60
704168000	150	6"	168,3	4,5	229	313	6,52	1	60
704193000	175	-	193,7	5,6	270	367	11,02	1	24
704219000	200	8"	219,1	6,3	305	414	15,96	1	24
704244000	-	-	244,5	6,3	340	462	19,77	1	12
704273000	250	10"	273	6,3	381	518	24,8	1	9
704323000	300	12"	323,9	7,1	457	619	39,82	1	9
704355000	350	14"	355,6	8	533	711	57,47	1	-
704406000	400	16"	406	8,8	610	813	82,6	1	-
704508000*	500	20"	508	11	762	1016	161	1	-
704609000*	600	24"	609	12,5	914	1219	271,38	1	-

Tolleranze dimensionali / Dimensional tolerances

D = ± 1% D MIN ± 0,5 mm

S = S ≤ 4 mm (-12,5% x S / +20% x S) S > 4 mm (-12,5% x S / +15% x S)

R = ± 2 mm ≤ DN 200 ± 3 mm > DN 200 ≤ DN 400 ± 14,5 mm DN 500 - 600

B = ± 7 mm ≤ DN 400 ± 6 mm DN 500 - 600

(*) Dimensioni non previste nella norma EN 10253-1 - Sizes not provided in EN 10253-1