

DRYFOOD ANTISTATIC D



Delivery hose suitable for powdery and granular dry food products. Hose tested according to the main norms for food contact materials (FCM – Reg. (CE) 1935/2004). Manufactured according to GMP (Reg. (CE) 2023/2006).

DESCRIPTION

Tube

NBR, white, antistatic ($R < 10^9 \Omega/m$), phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 CFR 177.2600; BFR XXI cat. 4; DM 21/03/1973 and subsequent amendments; REGULATION 1935/2004/CE.

Reinforcement

synthetic plies, on request a/s wires to discharge static electricity

Cover

smooth, black, conductive, cloth finish. Abrasion, ageing and ozone resistant

Marking

TUDERTECHNICA DRYFOOD ANTISTATIC

TECHNICAL CHARACTERISTICS

Temperature range: -25°C / +80°C (-13°F / +176°F)
Norm: ISO 1307 for dimensional tolerances



refer to guidelines for cleaning and sanitizing on Tudertechnica website



Inside diameter		Outside diameter		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
51	2,00	66	2,60	6	90	18	270	1,82	1,22	-	-
76	3,00	94	3,70	6	90	18	270	3,22	2,16	-	-
102	4,00	124	4,88	6	90	18	270	5,06	3,39	-	-
127	5,00	151	5,94	6	90	18	270	7,13	4,78	-	-
152	6,00	176	6,93	6	90	18	270	8,43	5,65	-	-

Data refer to ambient temperature (20°C). Other diameters, wall thickness and pressure only on specific request

REV-2021-06-04